

Biolum Plus Portable ATP Hygiene Monitoring System

Your smarter hygiene safety guardian



As the upgraded member of Tianlong's ATP hygiene monitoring family, Biolum Plus takes hygiene monitoring to the next level. The progressive testing swab ensures reliable results within seconds, which are clearly displayed on screen for instant evaluation. With enhanced software design and cloud-based data management system, it offers a more intuitive and convenient operation experi-

SMARTER HYGIENE MONITORING, POWERED BY THE CLOUD

Tianlong cloud-based data management software connects easily with Biolum Plus to collect, analyze, and visualize ATP data from multiple devices—anytime, anywhere. It streamlines workflows, strengthens risk control, and enhances hygiene monitoring efficiency.










One-click software updates

platform,no installation needed

Team collaboration with role-based access

management of one or multiple devices


management across sites



COMPATIBLE SWABS

QuickSwab

QuickSwab is a simple, all-in-one, pen-sized sampling device for surface cleanliness testing. It delivers exceptional accuracy and precision across a wide range of industrial applications.



LiquSwab

LiquSwab is a fast and reliable sampling tool designed for ATP testing in liquid samples. The swab is available in two formats: Free and Total. LiquSwab Free measures dissolved ATP that is free in liquid (non-microbial ATP). LiquSwab Total measures both free ATP and microbial ATP (non-microbial and microbial ATP) in the liquid. The difference between LiquSwab Total and Free provides an indication of microbial contamination in the samples.



ACCESSORIES

EternalLight-H

ATP Detector Optical Calibrator

Biolum Plus will ensure the test accuracy every time turning on the self-check function. Also, the additional calibration can be used to verify the accuracy by EternalLight-H. This calibration verification device is highly compatible with Tianlong Biolum, Biolum Plus and Biolum Pro ATP hygiene monitoring system.



SPECIFICATIONS

Model	Biolum Plus	
Dimensions	189mmx70mmx35mm	
Weight	315g	
Detection Limit	10 ⁻¹⁶ moles ATP	
Detection Deviation	±5% or±5 RLUs	
Self-calibration at Startup	15s or 60s	
Real-time Detection Time	10s/test	
Memory Capacity	256 test plans, 256 user IDs, 2000 test program and 10000 results	
Communication Interface	USB, Bluetooth, WiFi	
Test Repeatability	8%-20%	
Correlation Coefficient	R²≥0.995	
Power Supply	3.7V rechargeable lithium battery (charging limit voltage: 4.2V)	
Running Time	Continuously work for 10 h, standby for 600 h	
Operating Temperature Range	5-40°C	
Operating humidity Range	≤80% RH	

Swabs

Cat.No.	Swabs	Specification	Remark
A017H	QuickSwab	20 pieces/package	Surface test
A010H	LiquSwab Total	20 pieces/package	Liquid test (Total ATP)
A011H	LiquSwab Free	20 pieces/package	Liquid test (Free ATP)

Calibrator

Model	EternalLight-H	
Service life	5 years	
Battery	CR1025 lithium battery (3V)	

APPLICATION AREAS











Version 1.0

All rights reserved by Tianlong. October 14, 2025









Tianlong Science and Technology

Mail: inquiry@medtl.com Phone: +86-29-82682132 Website: www.medtl.net

Address: No. 4266 Shanglin Road, Xi'an, China